

UT353BT MINI SOUND LEVEL METER

- Range: 30dB ~ 130dB
- Accuracy: +/- 1.5dB
- Frequency Response: 31.5Hz ~ 8kHz
- Resolution 0.1dB
- Sampling Rate: Fast: 125ms, Slow: 1000ms
- Bluetooth App
- Bluetooth
- Data Hold
- APO
- MAX/MIN
- Low Battery Indication
- LCD Backlight
- Overload Indication

excl VAT **R829.00**
Incl VAT **R953.35**

UT12D DUAL AC VOLTAGE DETECTOR

- AC Voltage: 90V~1000V
- AC Voltage: 24V~1000V
- Sensitivity Switching: Auto
- APO
- Flashlight
- Audible/Visual Alarm
- Neutral & Live Line Distinction
- Indication LED: Green/Red

excl VAT **R195.00**
Incl VAT **R224.25**

2117R TRMS CLAMP METER

- AC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 40MΩ
- Capacitance: 6mF
- Frequency: 1MHz
- Auto Range
- Jaw Capacity >33mm
- Diode
- Data Hold
- APO
- LCD Backlight
- Continuity Buzzer
- Low Battery Indication
- 6000 Display Count

excl VAT **R1 199.00**
Incl VAT **R1 378.85**

UTi260B THERMAL IMAGER

- IR Resolution: 256 x 192 Pixels
- Display: 2.8" LCD
- Temperature Range: -15°C ~ 550°C
- Palettes: Iron, Rainbow, Grey
- NETD: ≤ 50mK
- Display Mode: Thermal; Visible; Blending
- Spatial Resolution: 3.8mrad
- Frame Rate: <25Hz
- PC Analysis Software
- FOV: 56°(h) * 42°(V)
- High and Low Temperature Tracking
- Photograph Function with SD Card Storage
- PC Analysis Software
- Buzzer/Flashlight Alarm
- Real-time Capture of Hi/Low Temperature
- Flashlight
- Tripod Mounting Hole

excl VAT **R11 999.00**
Incl VAT **R13 798.85**

UT33C+ PALM SIZE MULTIMETER

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 20MΩ
- Temperature: 1000°C
- APO
- Diode
- Continuity Buzzer
- LCD Backlight
- Relative Mode
- Probe Placing Slots
- LCD Size 53mm x 28mm
- 2000 Display Count

excl VAT **R379.00**
Incl VAT **R435.85**

LM70A LASER DISTANCE METER

- Range: 70m
- Measurement Units: m/ft/in
- Min. Display Unit: 0.001m
- Measurement Basis: Front/Rear
- Accuracy: +/- 2mm
- Laser Class: 2
- Laser Type: 630 ~ 670nm, <1mW
- Single Measurement
- Continuous Measurement
- MAX/MIN/AREA
- Volume
- Add/Subtract
- Horizontal Bubble
- Data Storage 99 Groups
- APO
- Display Type: LCD
- Display Size: 50mm
- Audio Indication
- Pythagoras
- Self Calibration
- Auto Laser Off

excl VAT **R879.00**
Incl VAT **R1 010.85**

excl VAT **R8 599.00**
Incl VAT **R9 888.85**

B10 THERMAL IMAGER

- Thermal resolution: 256 x 192 (49,152 pixels)
- NETD: < 40mK
- Temperature measurement range: -20°C ~ 550°C
- Measurement Presets: Center spot, Hot spot, Cold spot, User Preset Point
- FOV: 37.2° x 50°
- Spatial Resolution: 3.3mrad
- Focus Free
- Pixel Pitch: 12µm
- Colour Palettes: White Hot, Black Hot, Rainbow, Ironbow
- Free focus
- Image Mode: Thermal / Visual / Fusion / PIP
- 25 Hz image frequency
- USB Interface
- WiFi



UT123 POCKET SIZE HOUSEHOLD MULTIMETER

- AC/DC Voltage: 600V
- Resistance: 20MΩ
- Temperature: -40°C ~ 300°C
- Acousto-optic Indication
- Data Hold
- APO
- Continuity Buzzer
- Low Battery Indication
- NCV
- EBTV Screen
- 4000 Display Count

excl VAT **R415.00**
Incl VAT **R477.25**



UT161D TRMS MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 20A
- Resistance: 60MΩ
- Frequency: 10Hz ~ 10MHz
- Capacitance: 60mF
- Temperature: -40°C ~ 1000°C
- MAX/MIN
- Continuity Buzzer
- Relative Mode
- USB Communications
- Data Hold
- LCD Backlight
- Low Battery Indication
- Display Count 6000
- Diode
- hFE Transistor
- Analog Bar
- NCV
- LoZ ACV
- Auto Power Off

excl VAT **R2 495.00**
Incl VAT **R2869.25**

UT133B MULTIMETER

- AC/DC Voltage: 600 V
- DC Current: 10A
- Resistance: 60MΩ
- Capacitance: 9.9999mF
- APO
- Diode
- Continuity Buzzer
- Low Battery Indication
- Data Hold
- Overload Indication
- Test Probe Holder
- LCD Backlight
- Battery Test 1.5 & 9V
- NCV
- 6000 Display Count

excl VAT **R645.00**
Incl VAT **R741.75**



UT22B-EU VOLTAGE AND CONTINUITY TESTER

- Voltage Indication (V AC/DC): 6V ~ 1000V
- Frequency: 50/60Hz
- Voltage Indication
- Auto Detection of AC/DC
- Input Protection

excl VAT **R399.00**
Incl VAT **R458.85**

UT300S 400°C INFRARED THERMOMETER

- Temperature: -32 ~ 400°C
- Accuracy +/- 2°C
- Distance To Spot Ratio: 12:1
- Response Time 500ms
- Emissivity 0.10 ~ 1.00 Adjustable
- Selection °C/°F
- Display Hold
- APO
- Low Battery Indication
- MAX/MIN
- High Alarm
- Low Alarm
- LCD Backlight
- Auto Data Hold
- Optional (on/off) Laser Pointer
- Single Laser

excl VAT **R499.00**
Incl VAT **R573.85**

UT306A MINI INFRARED THERMOMETER

- Measurement Range: -35 ~ 300°C
- Distance To Spot Ratio 6:1
- Emissivity 0.95
- Response Time 250ms
- Spectral Response 8µm ~ 14µm
- Single-laser Targeting
- White Backlight
- MAX/MIN/AVG
- Lock Measurement
- Data Hold
- APO
- Low Battery Indication
- Power Off Memory
- Selection °C/°F

excl VAT **R679.00**
Incl VAT **R780.85**



UT501A 5.5GΩ INSULATION RESISTANCE TESTER

- Test Voltage 100/250/500/1000V
- Insulation Resistance (Ω) 5.5GΩ
- Short Circuit Current: <2mA
- AC Voltage (V) 750V
- Low Battery Indication
- Alarm Indication
- High Voltage Indication
- Auto Discharge
- 10mΩ Internal Resistance Test
- 2000 Display Count
- Auto Range
- LCD Backlight
- Alarm Buzzer
- Overload Indication

excl VAT **R2 299.00**
Incl VAT **R2 643.85**

UT61B+ MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 10A
- Resistance: 60MΩ
- Frequency: 10Hz ~ 10MHz
- Capacitance: 60mF
- MAX/MIN
- Diode
- Continuity Buzzer
- Relative Mode
- Analog Bar
- NCV
- Data Hold
- LCD Backlight
- Low Battery Indication
- Auto Power Off
- Display Count 6000

excl VAT **R1 599.00**
Incl VAT **R1 838.85**

UT202+ 400A TRMS CLAMP METER

- AC Current: 400A
- AC/DC Voltage: 600V
- Resistance 40MΩ
- Capacitance: 4000µF
- Temperature: -40°C ~ 1000°C
- MAX/MIN
- Relative Mode
- Display Size: 35 x 27mm
- Auto Ranging
- Jaw Capacity 28mm
- 4000 Display Count
- NCV
- Backlight
- Data Hold
- APO

excl VAT **R839.00**
Incl VAT **R964.85**

UT256B OPEN JAW TRMS CLAMP METER

- AC/DC Current: 200A
- DC Voltage: 1000 V
- AC Voltage: 750V
- Resistance: 60MΩ
- Capacitance: 60mF
- Auto Ranging
- APO
- Diode
- NCV
- Data Hold
- Zero Mode
- LCD Backlight
- Continuity Buzzer
- Input Protection
- Low Battery Indication
- Relative Mode
- 6000 Display Count

excl VAT **R2 159.00**
Incl VAT **R2 482.85**

UT89X TRMS MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 20A
- Resistance: 60MΩ
- Capacitance: 100mF
- Frequency: 10MHz
- Temperature: -40°C ~ 1000°C
- Continuity Buzzer
- Diode
- Low Battery Indication
- Transistor hFE
- Dual Range NCV Test
- Flashlight
- Audible / Visual Alarm
- Capacitor Charging Indicator
- Live Wire Test
- Relative Mode
- 6000 Display Count
- Data Hold
- Duty Cycle
- APO
- Input Alarm

excl VAT **R825.00**
Incl VAT **R948.75**

UT210A MINI CLAMP METER

- AC Current: 200A
- Jaw Capacity 16mm
- Data Hold
- LCD Backlight
- APO
- Auto Range
- Low Battery Indication
- 2000 Display Count

excl VAT **R725.00**
Incl VAT **R833.75**

UT681C CABLE TESTER RJ45/RJ11/BNC ADAPTER

- Cable Tester for RJ45/RJ11/BNC Adapter
- Fast-speed Test Mode LED1 ~ LED8, LED_G
- Slow-speed Test Mode LED1 ~ LED, LED_G
- Test for Short Circuit, Crossover, Open Circuit etc.
- Ethernet Cable - Shielded / Unshielded
- Manual Shutdown Function
- Single Key Operation
- Low Battery Detection
- APO
- 9V Battery

excl VAT **R639.00**
Incl VAT **R734.85**

UT522 EARTH GROUND TESTER

- Earth Resistance: 0 ~ 4000Ω
- AC Earth Voltage: 0 ~ 400V
- Manual Range
- Low Battery Indication
- Data Hold
- LCD Backlight
- Double Insulation Protection
- Contact Badness Indication
- Simple 2-Wire Testing
- Precision 3-Wire Testing
- Over-Range Display
- 4000 Display Count
- APO
- Data Storage 20
- Full Icon Display

excl VAT **R4 999.00**
Incl VAT **R5 748.85**

UT-USBC USB 3-in-1 CHARGING CABLE

- USB-A to USB-C, USB-MICRO and Lightning

excl VAT **R92.00**
Incl VAT **R105.80**