

Promotion runs from 1 February 2024 to 30 April 2024 or while stocks last. E & OE. www.uni-trend.co.za

UT206A+ TRMS CLAMP METER

- AC Current: 1000A
- AC/DC Voltage: 1000V
- Resistance: 60MΩ
- Capacitance: 60mF
- Frequency: 45Hz ~ 1kHz
- Temperature: -40°C ~ 1000°C
- Jaw Capacity > 40mm
- Inrush Current: 1000A
- Auto Range
- Diode
- NCV
- Data Hold
- MAX/MIN/REL
- LCD Backlight
- Continuity Buzzer
- APO
- Low Battery Indication
- 6000 Display Count



excl VAT **R1 899.00**
Incl VAT **R2 183.85**

UT18E VOLTAGE AND CONTINUITY TESTER

- AC/DC Voltage Display (V) 6V ~ 1000V
- Phase Rotation Test
- Continuity Test: Resistance 0~100kΩ, Beeper LED Light Indicator
- RCD Test
- Self-inspection
- No Power Test
- Polarity Detection
- Auto Range
- Low Battery Indication
- Over Voltage Protection



excl VAT **R1 495.00**
Incl VAT **R1 719.25**

UT658A USB TESTER

- Input & Output Ports: USB Type A
- Voltage Range: 4 - 24VDC
- Current Range: 0.05 ~ 3ADC
- Capacity: 0 ~ 99999mAh
- Energy: 0 ~ 1000Wh
- Circuit Equivalent Resistance Measurement: 1 ~ 480Ω
- USB Data Cable Voltage (D+, D-): 0 ~ 3.3V
- Data Storage 10
- Maximum Recording Time: 99h, 59min, 59sec
- Fast Charge Protocol: Type A: Supports USB 2.0 Data Transmission & QC1.0/2.0/3.0 Fast Charge Protocol



excl VAT **R295.00**
Incl VAT **R339.25**

POCKET2 HANDHELD THERMAL IMAGING CAMERA

- IR Resolution: 256 x 192 (49,152pi)
- NETD: <40 mK
- FOV: 50° x 37.2° (H x V)
- Display: 640 x 480 Resolution, 3.5" LCD Touch Screen
- Object Temperature Range: -20°C ~ 400°C
- Accuracy: +/- 2°C
- WiFi: 802.11 b/g/n
- Image Resolution: Configurable: 2MP, 5MP, 8MP
- Focus: Fixed
- IFOV: Fixed
- Image Frequency: 25Hz
- Image Mode: Thermal / Optical / Fusion / PIP / Blending
- Colour Palettes: Black Hot; White Hot; Rainbow; Ironbow; Red Hot; Fusion; Rain
- Built-In 16GB Internal Memory



excl VAT **R13 699.00**
Incl VAT **R15753.85**



UT306C INFRARED THERMOMETER

- Circle Laser
- Temperature: -50°C ~ 500°C
- Accuracy: +/- 2°C
- D:S Ratio: 12:1
- EBTN Display
- Emissivity: 0.1 ~ 1.0 Adjustable
- °C/°F Selection
- High/Low Temperature Alarm
- Laser On/Off
- APO
- Low Battery Indication
- MAX/MIN/AVG/DIFF Modes
- Response Time: 500s
- Data Hold



excl VAT **R489.00**
Incl VAT **R562.35**

UT256 AC/DC FORK METER

- AC/DC Current: 60A
- NCV
- Data Hold
- Zero Mode
- LCD Backlight
- APO
- Audible and Visual Alarm
- Low Battery Indication
- Relative Mode



excl VAT **R925.00**
Incl VAT **R1 063.75**



UT387D WALL SCANNER

- Detect Principle: Electro-Magnetic Induction
- Detects Wooden Beams, Metal Objects, Electrical Wire
- Metals Scan Depth: 100mm - Iron Pipe 80mm - Brass Pipe
- Stud-scan Depth (Wood): 38mm
- Thick-scan Depth (Wood): 50mm
- AC Electrical Wire Depth: 50mm
- Voice Notification
- APO
- Low Battery Indication

excl VAT **R1 399.00**
Incl VAT **R1 608.85**



UT682D WIRE TRACKER

- Wire Types: Telephone Lines/Twisted Pair/Electric Wire
- Telephone Wire Test Distance ≥3000m
- Polarity Indication for Phone Lines
- Transmitter Output Voltage: 8V DC
- Transmitter Power Supply: 9V Battery
- Receiver Power Supply: 9V Battery
- Polarity Indication for Telephone Wires
- Max Receiver Operating Current 40mA
- Max Receiver Standby Current 10mA

excl VAT **R699.00**
Incl VAT **R803.85**



UT-L13 DOUBLE INSULATED TEST LEADS

- Cable Length: 900mm
- Standard Banana Interface: Ø4mm
- Body Length: 128mm
- Probe Length: 18mm
- CAT Rating: CATIV600V
- Recommended Alligator Clips: UT-C02A / UT-C04A
- Double Insulation
- UL Authenticated
- Removable Insulation Cap

excl VAT **R215.00**
Incl VAT **R247.25**

UT333BT MINI TEMPERATURE HUMIDITY METER

- Temp Range: -10 ~ 60°C
- Temperature Resolution 0.1°C
- Humidity Range: 0 ~ 100%RH
- Humidity Resolution 0.1%RH
- Sampling Rate 1/s
- APP
- Bluetooth
- APO
- Data Hold
- Low Battery Indication
- MAX/MIN
- LCD Backlight
- Power ON/OFF
- Overload Indication
- Unit Selection °C/°F



excl VAT **R729.00**
Incl VAT **R838.35**



UT201+ 400A TRMS CLAMP METER

- AC Current: 400A
- AC/DC Voltage: 600V
- Resistance 40MΩ
- Display Size: 35 x 27mm
- Backlight
- MAX/MIN
- Data Hold
- Continuity Test
- Low Voltage Indicator
- Jaw Capacity 28mm
- 4000 Display Count
- NCV
- Auto Ranging
- Diode

excl VAT **R729.00**
Incl VAT **R838.35**



UT892 2000V AC/DC HIGH VOLTAGE DIGITAL MULTIMETER

- AC/DC Voltage: 2000 V
- Variable Frequency Voltage: 600V
- Resistance: 60MΩ
- Capacitance: 60mF
- Live Test
- Diode
- Relative Mode
- Data Hold
- Auto Power Off
- Frequency: 10Hz ~ 10kHz
- Auto Range
- MAX/MIN
- Continuity Buzzer
- NCV
- Low Battery Indication
- Display Count 6000

excl VAT **R1 069.00**
Incl VAT **R1 229.35**

UT-C02A ALLIGATOR CLIPS

- Through Hole Alligator Clip
- Length: 80mm
- Clip Opening: 36mm
- CAT Rating: CATIII 1000V, CAT IV 600V 10A
- Recommended Test Leads: UT-L13



excl VAT **R225.00**
Incl VAT **R258.75**

B20 THERMAL IMAGER

- Thermal resolution: 256 x 192 (49 152 pixels)
- SuperIR: 320 x 240
- NETD: < 40mK
- Temperature measurement range: -20 °C ~ 550 °C
- Measurement Presets: Center spot, Hot spot, Cold spot, User Preset Point/ Line/Area
- FOV: 37.5° x 50.0°
- Pixel Pitch: 17µm
- Colour Palettes: White Hot, Black Hot, Rainbow, Ironbow, Red hot, Fusion, Rain
- Fixed focus
- Image Mode: Thermal / Optical / Fusion / PIP
- 25 Hz image frequency
- WiFi



excl VAT **R13 969.00**
Incl VAT **R16 064.35**

UT196 1700V DC TRUE RMS PROFESSIONAL MULTIMETER- SOLAR PRO

- AC Voltage: 1500 V
- DC Voltage: 1700 V
- Resistance: 60MΩ
- Frequency: 1MHz
- Capacitance: 60mF
- True RMS
- Data Hold
- Dual Display
- Low Pass Filter
- Auto Range
- MAX/MIN
- Continuity Buzzer
- Relative Mode
- Analog Bar
- Flashlight Backlight
- Low Battery Indication
- Auto Power Off
- Display Count 6000
- NCV
- Diode
- NCV
- Flashlight
- Low Battery Indication
- High Voltage Warning
- 6000 Display Count



excl VAT **R3 755.00**
Incl VAT **R4 318.25**



UT208B TRMS CLAMP METER

- AC/DC Current: 1000A
- Resistance: 60MΩ
- Frequency: 10Hz ~ 1MHz
- Temperature: -40°C ~ 1000°C
- Auto Range
- Jaw Capacity 42mm
- Inrush Current
- Data Hold
- MAX/MIN/REL
- Continuity Buzzer
- Overload Indication
- 6000 Display Count
- AC/DC Voltage: 1000V
- Capacitance: 60mF
- APO
- Diode
- NCV
- Flashlight
- LCD Backlight
- Low Battery Indication
- High Voltage Warning

excl VAT **R2 999.00**
Incl VAT **R3 448.85**

UT593 COMPLIANCE TESTER - MULTI FUNCTIONAL

- AC Voltage: 440V
- Insulation Test: 250/500/1000V
- Prospective Short Circuit: 26kA
- RCD Test Current: 10/30/100/300/500mA
- Low Ohm Measurement
- ELCB Test (Time & Sensitivity)
- LCD Backlight
- Phase Switch (RCD) 0 ~ 180°
- Auto Half-wave Test
- DC Voltage: 440V
- Phase Rotation
- Loop Impedance
- APO
- Low Battery Indication
- Data Logging
- 10 000 Display Count



excl VAT **R12 699.00**
Incl VAT **R14 603.85**

UT136C+ MULTIMETER

- AC/DC Voltage: 1000 V
- AC/DC Current: 10A
- Resistance: 40MΩ
- Capacitance: 40mF
- Frequency: 400Hz ~ 40MHz
- Temperature: -40°C ~ 1000°C
- APO
- Data Hold
- hFE Transistor Test
- Diode
- NCV
- Low Battery Indication
- Overload Alarm
- Test Probe Holder
- Backlight
- 4000 Display Count



excl VAT **R799.00**
Incl VAT **R918.85**



M30 HANDHELD THERMOGRAPHY CAMERA

- Thermal resolution: 384 x 288 (110 592 pixels)
- Temperature measurement range: -20 °C ~ 550 °C
- Accuracy: Max (±2°C ±2%),
- FOV: 37.5° x 28.5°
- Measurement Presets: Center spot, Hot spot, Cold spot, User Preset Point/Line/Area
- Pixel Pitch: 17µm
- Colour Palettes: White Hot, Black Hot, Rainbow, Ironbow, Red hot, Fusion, Rain
- Manual focus
- 25 Hz image frequency
- Bluetooth
- USB Interface
- NETD: < 35mK
- Image Mode: Thermal / Optical / Fusion / PIP
- 3.5" LCD touch screen display
- www.hikmicrotech.com/en/download/5

excl VAT **R54 889.00**
Incl VAT **R63 122.35**